

MULTI PURPOSE ATF

PRODUCT CODE: 1676

DESCRIPTION

49 NORTH® MULTI PURPOSE ATF is engineered to meet the current warranty requirements of General Motors and Ford. 49 NORTH® MULTI PURPOSE ATF is a multi-function, multi-viscosity "all weather" hydraulic fluid that meets the performance requirements of Denison, Sperry and Vickers.



QUALITIES

49 NORTH® MULTI PURPOSE ATF is formulated using selected high quality base stocks and premium additives. It is compatible with other approved fluids. 49 NORTH® MULTI PURPOSE ATF is engineered to provide superior protection and performance. It is inhibited for longer service life and protects transmission parts against rust, corrosion, and wear. It is dyed red for leak detection purposes.

APPLICATIONS

49 NORTH® MULTI PURPOSE ATF is recommended where the following obsolete specifications are required: GM Dexron®, Dexron®-IIE, Dexron®-IIIH and Dexron®-IIIH; Ford MERCON®, Type H and Type CJ; Allison C-3 and C-4; Caterpillar TO-2; and Daimler-Benz DKA. This multi-function fluid is also used industrially as a multi-viscosity "all weather" hydraulic fluid meeting the performance requirements of: Denison HF-0, HF-1, and HF-2; Sperry Vickers M-2950-S and I-286-S; Caterpillar TO-2 (SAE 10W); Renk Doromat 873 and 874; and Allison Type C-3 and C-4.

TYPICAL PROPERTIES

SAE Viscosity Grade	5W20
Product Code	1676
API Gravity (ASTM D-287)	31.7
Specific Gravity at 60 °F	0.8671
Density (lbs./gal.)	7.2
Viscosity (ASTM D-445):	
cSt @ 40° C	31-37
cSt @ 100° C	7.0-7.5
Viscosity Index	181
Pour Point (ASTM D-97), °F (°C)	-55(-48)
Flash Point (ASTM D-92), °F (°C)	363 (184)
Colour (Observed)	Red

PACKAGE SIZES

Available in bulk, 1211 L totes, 208 L drums, 20 L pails, 6x4 L cases, 12x1 L cases

CONTACT

Email: info@49northlubricants.com
www.49northlubricants.com

Phone: 780.986.9260
 Toll Free: 1.800.463.0354
 Fax Toll Free: 1.877.917.4949

6611 - 45 Street
 Leduc, Alberta
 Canada T9E 7E3