

XHVI SYNTHETIC BLEND HYDRAULIC FLUID

PRODUCT CODE: 45666

DESCRIPTION

49 NORTH® XHVI HYDRAULIC OIL is a synthetic blend hydraulic oil designed for use in the most demanding hydraulic systems. Its extremely high viscosity index allows hydraulic systems to start easily at low temperatures without cavitation while retaining its viscosity at high temperatures, and a potent ZDDP antiwear package reduces pump and component wear.

QUALITIES

49 NORTH® XHVI HYDRAULIC OIL is a long life fluid that provides maximum component protection and versatility. 49 NORTH® XHVI HYDRAULIC OIL has an advanced additive package that provides superior anti-wear qualities, rust preventatives, defoamant and oxidation inhibitors, and is non-corrosive to brass or bronze.

APPLICATIONS

49 NORTH® XHVI HYDRAULIC OIL is recommended for a wide range of hydraulic systems utilizing all types of pumps. 49 NORTH® XHVI HYDRAULIC OIL is ideal for mobile equipment subjected to extreme operating temperatures. The product is used in many types of hydraulic applications including construction, logging, farming, aerial work platforms, man-lifts, cranes, excavators and stationary hydraulic systems.

TYPICAL PROPERTIES

ISO Viscosity Grade	32
Product Code	45666
Specific Gravity (ASTM D-1298)	0.863
Density (lbs./gal.)	7.19
Viscosity (ASTM D-445):	
cSt @ 40° C	32.0
cSt @ 100° C	7.8
Viscosity Index	228
Pour Point (ASTM D-97), °C	-42
Flash Point (ASTM D-92), °C	203
Operating Range, °C	-38 to 80

PACKAGE SIZES

Available in Bulk, 1211 L Totes, 208 L Drums, 20 L Pails.

CONTACT

Email: info@49northlubricants.com
www.49northlubricants.com

Phone: 780.986.9260
Toll Free: 1.800.463.0354
Fax Toll Free: 1.877.917.4949

6611 - 45 Street
Leduc, Alberta
Canada T9E 7E3