

MULTI PURPOSE ENGINE OIL

PRODUCT CODE: 63025, 63029, 63030

DESCRIPTION

49 NORTH® MULTI PURPOSE ENGINE OILS are a proven engine lubricant designed for high output diesel and older gasoline engines operating under severe service conditions. Trouble free service in agricultural, commercial, and industrial applications demonstrates the effectiveness of 49 NORTH® MULTI PURPOSE ENGINE OILS.

QUALITIES

49 NORTH® MULTI PURPOSE ENGINE OILS are formulated with high quality base stocks and a proven additive system with the proper balance of metallic detergents, dispersants, and multipurpose inhibitors. 49 NORTH® MULTI PURPOSE ENGINE OILS have demonstrated reduced engine deposits, stable viscosity at extremely high shear stress and high temperature operating conditions, extremely low wear metals with extended drain intervals, superior corrosion protections, excellent Total Base Number retention, and controlled oil consumption.

APPLICATIONS

49 NORTH® MULTI PURPOSE ENGINE OILS cover a wide variety of applications in agricultural, commercial, and industrial uses. 49 NORTH® MULTI PURPOSE ENGINE OILS are formulated to meet or exceed a variety of specifications and engine manufacturers including:

- API Service Categories as listed in the typical properties
- Older two and four stroke diesel engines calling for a SAE 30 or SAE 40 grade
- ALLISON: C-3 & C-4 (SAE 10W only)

FEATURES & BENEFITS

Excellent cold flow properties provide faster lubrication during cold starts, maximizing engine life.

Mixed fleet service for both gasoline and diesel engines reduces misapplication.

Superb deposit engine tests have demonstrated outstanding engine cleanliness in critical areas.

Prevents wear by providing stable viscosity in high temperature, high load conditions.

Improved oxidation and rust protection throughout the drain interval.

CONTACT

Email: info@49northlubricants.com
www.49northlubricants.com

Toll Free: 1.800.463.0354
Facsimile: 780.986.9650

6611 - 45 Street
Leduc, Alberta
Canada T9E 7E3

TYPICAL PROPERTIES

SAE Viscosity Grade	10W	30	40
Product Code	63025	63029	63030
API Service	CF	CF, CF-2, SE	CF, CF-2, SE
Viscosity, Kinematic			
cSt @ 40°C	45	92	124
cSt @ 100°C	7.3	11.5	14.6
Viscosity Index	130	114	113
API Gravity	31.7	29.2	28.8
Pour Point, °C (°F)	-38 (-38)	-32 (-28)	-33 (-26)
Zinc, wt%	0.11	0.11	0.11
Sulfated Ash, wt%	0.8	0.8	0.8
TBN, ASTM D2896	8	8	8

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

HEALTH & SAFETY

A complete Safety Data Sheet (SDS) is available upon request.

PACKAGE SIZES

Available in Bulk, 1211L totes, 208L Drums, 20L Pails

CONTACT

Email: info@49northlubricants.com
www.49northlubricants.com

Toll Free: 1.800.463.0354
 Facsimile: 780.986.9650

6611 - 45 Street
 Leduc, Alberta
 Canada T9E 7E3