

MULTI-PURPOSE AUTOMATIC TRANSMISSION FLUID

PRODUCT CODE: 1676

DESCRIPTION

49 NORTH® MULTI-PURPOSE ATF meets the special frictional characteristics, transmission cleanliness and low temperature pumpability required for pre-2006 GM and Ford vehicles.

QUALITIES

49 NORTH® MULTI-PURPOSE ATF uses carefully selected base oils to ensure excellent low temperature performance as required by GM and Ford. The specialized performance additive provides superior oxidation resistance for extended use under high temperature operating conditions and smooth power transfer during shift cycles. 49 NORTH® MULTI-PURPOSE ATF contains special additives to prevent oil seal deterioration and provide superior resistance to foaming. The superb frictional properties needed in GM and Ford ATF fluids, which affect the shift feel, are retained for an extended period of time.

There is an increasing trend toward manufacturers using ATF for hydraulic applications, especially in cold weather environments. The superior anti-wear performance built into 49 NORTH® MULTI-PURPOSE ATF assures proper protection of these hydraulic pumps and systems where Dexron, Dexron II, Dexron III, and Mercon fluids are recommended by the manufacturer.

APPLICATIONS

49 NORTH® MULTI-PURPOSE ATF is recommended for use in all applications where manufacturers recommend:

- Dexron® III-HG
- Dexron® II, IIE
- Dexron®
- Type A, Suffix A
- Mercon®
- Ford M2C-138CJ
- Ford M2C-166H
- Ford Type H
- Allison C-4

49 NORTH® MULTI-PURPOSE ATF should not be used in applications calling for Dexron VI, Mercon V, SP, and Type F, Chrysler ATF +3, +4, CVT, and 6-speed transmissions.

CONTACT

Email: info@49northlubricants.com
www.49northlubricants.com

Toll Free: 1.800.463.0354
Facsimile: 780.986.9650

6611 - 45 Street
Leduc, Alberta
Canada T9E 7E3

FEATURES & BENEFITS

Outstanding frictional characteristics provide smooth shifting and excellent retention of performance throughout the service interval.

Excellent oxidation and sludge protection for high transmission temperatures experienced by modern cars.

Superior cold temperature flow characteristics assures ease of pumping and good shifting capabilities.

TYPICAL PROPERTIES

ISO Viscosity Grade	32
Product Code	1676
Colour	Red
API Gravity (ASTM D-1298)	32.8
Pour Point (ASTM D-97), °F (°C)	-54 (-48)
Flash Point (ASTM D-92), °F (°C)	417 (214)
Rust (ASTM D-665)	Pass
Oxidation (ASTM D-943), Hours	2000+
Viscosity	
cSt @ 40 °C	34.4
cSt @ 100 °C	7.0
Viscosity Index	171
Brookfield @ -40 cP	18,000

The typical properties listed reflect the general characterizes of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

HEALTH & SAFETY

A complete Safety Data Sheet (SDS) is available upon request

PACKAGE SIZES

Available in bulk, 1211 L totes, 208 L drums, 20 L pails, 6x 3.78L cases, 12x 1L cases.

CONTACT

Email: info@49northlubricants.com
www.49northlubricants.com

Toll Free: 1.800.463.0354
Facsimile: 780.986.9650

6611 - 45 Street
Leduc, Alberta
Canada T9E 7E3