

SAFETY DATA SHEET 49N PREMIUM GEAR LUBRICANTS

Revision Date: 06-12-2018

Section 1. Identification

Product Identifier

Product Name 49N Premium Gear Lubricants Common Name Gear Oil – 80W90 / 85W140 / 75W90

Product Code(s) 31310 / 31320 / 31330

Recommended or Restricted Uses

Recommended Use Lubricant
Restricted Use Not Applicable

Canadian Supplier

Supplier 49 North Lubricants

6611 45th Street, Leduc, Alberta T9E 7E3 Canada

Tel: (780) 986-9260 Fax: (780) 986-9650

Emergency Telephone Number

Emergency Telephone CHEMTREC: 1-800-424-9300

Section 2. Hazard Identification

Hazard Classification

WHMIS Regulatory Status Not Regulated

Physical Hazards Not Classified Health Hazards Not Classified Environmental Hazards Not Classified

Label Elements Not Applicable
Other Hazards Not Applicable

Section 3. Composition / Information on Ingredients

Composition

Component Highly-refined paraffinic petroleum oil Petroleum Additives

CAS Registry # Mixture Mixture
Concentration 95-99% 1-5%

Section 4. First Aid Measures

Route of Exposure

Inhalation: Move affected person to fresh air and keep warm and at rest. Loosen tight clothing such as collar, tie or belt.

If breathing becomes difficult, properly trained personnel can assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing continues.

Skin Contact: Rinse affected area with soap and water. Remove contaminated clothing.

Eye Contact: Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart.

Continue to rinse for at least 10 minutes

Ingestion: Do not induce vomiting. Do not give anything via mouth. Seek medical attention immediately.

Most Important Systems and Effects

Inhalation: May Cause: Coughing,

Skin Contact: May Cause: Temporary Skin Irritation

Eye Contact: May Cause: Irritation or Redness in Eyes

Ingestion: May Cause: Discomfort

Immediate Medical Attention and Special Treatment

Note for the Doctor Treat Symptomatically

Section 5. Fire-Fighting Measures

Extinguishing Media

Suitable Extinguishing Media Extinguish with dry chemical, foam, carbon dioxide powder or water fog.

Unsuitable Extinguishing Media Not Applicable

Specific Hazards Arising from the Hazardous Product

Specific hazards Containers can burst violently or explode when heated. Contains Hydrocarbons.

The product is immiscible with water and will spread on the water surface.

Hazardous combustion

products

Hydrocarbons. Carbon Monoxide (CO). Carbon Dioxide (CO₂).

Advice for Firefighters

Protective actions during firefighting

Avoid breathing gases or vapours. Evacuate the area. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done

without risk.

Special protective equipment

for firefighters

Not Applicable.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

Personal precautions Keep unnecessary and unprotected personnel away from spillage. Wear protective clothing as described

in Section 8. Follow safe handing as described in Section 7. Wash thoroughly after dealing with a spill. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch

or walk into spilled material.

Methods and Material for Containment and Cleaning Up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. For small spillages: wipe up with an absorbent

cloth. Avoid discharge into drains or watercourses or onto the ground. For large spillages: Contain the spilled material, removed and dispose of contaminated material with a licensed waste disposal site. If environmental pollution occurs (sewers, waterways, soil or air) inform the relevant authorities.

Large spills may require pumping of water or excavation of soil to clean up.

Methods for containment Use berms, skimmers, and absorbent to contain the spillage where appropriate. Ensure that wildlife

is deterred from entering the contaminated area.

Section 7. Handling and Storage

Precautions for Safe Handling

Usage precautions Read and follow manufacturer's recommendations. Wear PPE as described in Section 8. Eating, drinking, and

smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash before eating, drinking or smoking. Handle all packages and containers carefully. Keep all containers

tightly sealed when not in use.

Conditions for Safe Storage, Including any Incompatibilities

Storage Precautions Store away from incompatible materials listed in Section 10. Store in accordance with local regulations.

Keep containers in a cool, well ventilated location. The storage area floor should be leak-tight and

not absorbent. Do not store in direct sunlight. Empty containers may contain product residue and should be

stored accordingly.

Storage Class Not Applicable

Section 8. Exposure Controls / Personal Protection

Control Parameters

Occupational Exposure Limits 5 mg/m³ (8 hours)

Appropriate Engineering Controls

Engineering controls Provide adequate ventilation. Use engineered ventilation to keep the airborne concentration below the

recommended exposure limits.

Individual Protection Measures

General All personal protective equipment (PPE) should comply with Canada OH&S Regulations (SOR/86-304)

Eye/Face protection Recommended: Safety glasses. Where splash hazards exist use a face shield as well.

Hand protection Recommended: Neoprene or heavy nitrile gloves.

Body protection Recommended: Long sleeved coveralls.

Respiratory protection Vapourization is not expected at ambient temperatures. If engineered ventilation is inadequate, use a NIOSH-

certified respirator with a dual cartridge for organic vapor and P95 particulates.

Section 9. Physical and Chemical Properties

Physical Properties

Physical State Liquid
Colour Amber

Odour Mild Petroleum
Odour threshold Not Available

Chemical Properties

pH Not Available
Melting point / freezing point Not Available

Flash point > 205 °C (Closed Cup)
Evaporation rate <1 (butyl acetate = 1)

Flammability (solid; gas)

Lower Explosive Limit

Upper Explosive Limit

Vapour pressure

Vapour density

Relative density

Not Available

Not Available

Vol.13 kPa @ 20°C

Vapour density

Not Available

Variable

Variable

Value

Va

Solubility Insoluble in water

Partition coefficient: n-octanol/water

Not Available

Decomposition temperature Not Available Not Available Viscosity

Section 10. Stability and Reactivity

Not Available Reactivity

Stability Stable

Possibility of hazardous

Not Applicable

reactions

Conditions to avoid **Not Applicable Incompatible Materials Strong Oxidizers** Hazardous decomposition Not Applicable

products

Section 11. Toxicological Information

Routes of Exposure Ingestion, Inhalation, Skin/Eye Contact

Symptoms

Skin/Eye contact may cause irritation or redness **Physical**

Ingestion may cause discomfort

No Available Data Chemical **Toxicological** No Available Data

Exposure Effects

Delayed Effects No Available Data **Chronic Effects** No Available Data

Acute Toxicity Estimates (ATE)

ATE oral (mg/kg) No Available Data ATE dermal (mg/kg) No Available Data No Available Data ATE inhalation (mg/L)

Section 12. Ecological Information

No Available Data.

Section 13. Disposal Considerations

No Available Data. Follow Local Regulations.

Section 14. Transport Information

Not Applicable.

Section 15. Regulatory Information

Not Applicable.

Section 16. Other Information

SDS Revision Date: 06-12-2018

SDS Number(s) 31310 / 31320 / 31330

Disclaimer: The information contained herein is accurate to the best of our knowledge.