

Proudly Serving Canadian Industry Since 1984

ARCTIC EXTREME ISO 13 HYDRAULIC FLUID

PRODUCT CODE: 42222

DESCRIPTION

49 NORTH® ARCTIC EXTREME ISO 13 HYDRAULIC FLUID is an extremely high viscosity antiwear hydraulic fluid, recommended for all types of hydraulic systems operating under extremely low ambient temperatures. This product conforms to the extreme arctic viscometric requirements of MIL 5606-A spec.

QUALITIES

49 NORTH® ARCTIC EXTREME ISO 13 HYDRAULIC FLUID has very high viscosity index with excellent shear stability, ensuring a thick lubricating film and hydraulic pump efficiency during the full life of the fluid. Good compatibility with elastomers and seals, and excellent demulsibility with water. Extremely low pour point and superior low temperature flow characteristics prevent pump cavitation during start-up. Excellent antifoam, corrosion protection, and anti-oxidation properties. Dyed red for easy identification.

APPLICATIONS

49 NORTH® ARCTIC EXTREME ISO 13 HYDRAULIC FLUID is specifically designed to be used in all types of hydraulic pumps and motors that require the use of antiwear hydraulic oils. It is suitable for hydraulic systems working under extremely low temperatures and permits easy startup in arctic conditions. This product does not meet aviation requirements.

TYPICAL PROPERTIES

| ISO Viscosity Grade | 13 |
|--------------------------------------|------------|
| Product Code | 42222 |
| Specific Gravity (ASTM D-1298) | 0.86 |
| | |
| Density (lbs./gal.) | 7.16 |
| Viscosity (ASTM D-445): | |
| cSt @ 40° C | 14.17 |
| cSt @ 100° C | 4.98 |
| Viscosity Index | 337 |
| Brookfield Viscosity (D-2983): | |
| cPs @ -40° C | 700 |
| Pour Point (ASTM D-97), °F (°C) | -85 (-65) |
| Flash Point (ASTM D-92), °F (°C) | 205 (96) |
| Colour (Visual) | Red |
| Dielectric Strength, KV (ASTM D-887) | 45* |
| Approximate operating range, °F | -50 to 115 |

^{*}Dielectric strength is at the point of manufacture. To maintain dielectric strength avoid exposure to moisture and dirt.

PACKAGE SIZES

Available in 1211 L totes, 208 L Drums, 20 L Pails.

CONTACT

Email: info@49northlubricants.com www.49northlubricants.com

Phone: 780.986.9260
Toll Free: 1.800.463.0354
Fax Toll Free: 1.877.917.4949

6611 - 45 Street Leduc, Alberta Canada T9E 7E3