



Proudly Serving Canadian Industry Since 1984

FIFTH WHEEL GREASE

PRODUCT CODE: 5406

DESCRIPTION

49 NORTH® FIFTH WHEEL GREASE is a premium product formulated for the harsh environment encountered in fifth wheel applications, and contains molybdenum disulfide to ensure a high load carry capacity.

QUALITIES

49 NORTH® FIFTH WHEEL GREASE is formulated with rust and corrosion inhibitors, molybdenum disulfide, and a high quality base oil to ensure that this product will outlast conventional products in a fifth wheel application.

APPLICATIONS

49 NORTH® 49 NORTH® FIFTH WHEEL GREASE can be used in all heavy duty fifth wheel applications, as well as:

- All fifth wheel top plates (Heavy, Medium, and Light duty)
- King pins
- Fifth wheel slides
- Axle slides
- Trailer Balls

FEATURES & BENEFITS

Easy to use

Long Lasting

Water Resistant



Email: info@49northlubricants.com www.49northlubricants.com

Toll Free: 1.800.463.0354 Facsimile: 780.986.9650 6611 - 45 Street Leduc, Alberta Canada T9E 7E3



NLGI Grade Product Code Texture Color, Observed Worked 60 Penetration (ASTM D217) Dropping Point (ASTM D2265) °C Weld Load, kg (ASTM D2509) Timken OK Load, lbs (ASTM D2509) Moly Content, % 1.5 5406 Smooth, Tacky Dark Green 295-310 243 315 kg 60 lbs 0.75

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

HEALTH & SAFETY

A compete Safety Data Sheet (SDS) is available upon request. Used oil contains by-products which may be harmful.

PACKAGE SIZES

Available in 181kg Drums, 55kg Kegs, 15kg pails



CONTACT

Email: info@49northlubricants.com www.49northlubricants.com

Toll Free: 1.800.463.0354 Facsimile: 780.986.9650 6611 - 45 Street Leduc, Alberta Canada T9E 7E3