Safety Data Sheet



SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Delo Syn-Trans XV SAE 75W-80

Product Use: Automotive Gear Lubricant

Product Number(s): 223080

Company Identification Chevron Canada Limited 500 - 5th Ave. SW

Calgary, ALBERTA T2P 0L7

Canada

www.chevronlubricants.com

Transportation Emergency Response

CHEMTREC: (800) 424-9300 or (703) 527-3887

Health Emergency

Chevron Emergency & Information Center: Located in the USA. International collect calls accepted. (800) 231-

0623 or (510) 231-0623 **Product Information**

email: lubemsds@chevron.com

Product Information: (800) LUBE TEK

SECTION 2 HAZARDS IDENTIFICATION

CLASSIFICATION: Acute aquatic toxicant: Category 3. Chronic aquatic toxicant: Category 3.

Environmental Hazards: Harmful to aquatic life with long lasting effects (H412).

PRECAUTIONARY STATEMENTS:

Prevention: Avoid release to the environment (P273).

Disposal: Dispose of contents/container in accordance with applicable local/regional/national/international

regulations (P501).

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT

Revision Number: 2 Delo Syn-Trans XV SAE 75W-80

Revision Date: October 25, 2019 SDS: 35727

Highly refined mineral oil (C15 - C50)	Mixture	5 - 10 %wt/wt
Phosphoric acid ester, amine salt	Mixture	0.5 - 1.5 %wt/wt

Note that the actual concentration or concentration range of some or all of the above ingredients is considered confidential business information and is being withheld as permitted by WHMIS 2015.

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

Most important symptoms and effects, both acute and delayed IMMEDIATE HEALTH EFFECTS

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.

Ingestion: Not expected to be harmful if swallowed.

Inhalation: Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

Indication of any immediate medical attention and special treatment needed Not Applicable

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions: This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Phosphorus, Nitrogen, Sulfur.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures: Eliminate all sources of ignition in vicinity of spilled material.

 Revision Number:
 2
 Of
 7
 Delo Syn-Trans XV SAE 75W-80 SDS:
 35727

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. **Reporting:** Report spills to local authorities as appropriate or required.

SECTION 7 HANDLING AND STORAGE

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

ENGINEERING CONTROLS:

Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

Skin Protection: No special protective clothing is normally required. Where splashing is possible, select protective clothing depending on operations conducted, physical requirements and other substances in the workplace. Suggested materials for protective gloves include: Chlorinated Polyethylene (or Chlorosulfonated Polyethylene), Nitrile Rubber, Viton.

Respiratory Protection: No respiratory protection is normally required.

If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

Occupational Exposure Limits:

Component	Country/	Form	TWA	STEL	Ceiling	Notation
	Agency					
Highly refined mineral oil (C15 - C50)	ACGIH		5 mg/m3	10 mg/m3		

NOTE ON OCCUPATIONAL EXPOSURE LIMITS: Consult local authorities for acceptable provincial values in Canada. Consult the Canadian Standards Association Standard Z94.4-2011 Selection, Use and Care of Respirators.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

 Revision Number:
 2
 Delo Syn-Trans XV SAE 75W-80

 Revision Date:
 October 25, 2019
 3
 of SDS:
 35727

Attention: the data below are typical values and do not constitute a specification.

Color: Light to Brown
Physical State: Liquid
Odor: Hydrocarbon odor
Odor Threshold: Not available

pH: Not available

Vapor Pressure: Not available

Vapor Density (Air = 1): Not available
Initial Boiling Point: Not available

Solubility: Soluble in hydrocarbon solvents; insoluble in water.

Freezing Point: Not available **Melting Point:** Not available

Specific Gravity: 0.85 @ 15.6°C (60.1°F) (Typical)

Density: 0.85 kg/l @ 15°C (59°F) (Typical) **Viscosity:** 54 mm2/s @ 40°C (104°F) (Typical)

Evaporation Rate: Not available

Decomposition temperature: Not available **Octanol/Water Partition Coefficient:** Not available

FLAMMABLE PROPERTIES:

Flammability (solid, gas): Not Applicable

Flashpoint: (Cleveland Open Cup) 200 °C (392 °F) (Minimum)

Autoignition: Not available

Flammability (Explosive) Limits (% by volume in air): Lower: Not available Upper: Not available

SECTION 10 STABILITY AND REACTIVITY

Reactivity: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc. **Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and

handling conditions of temperature and pressure.

Incompatibility With Other Materials: Not applicable

Hazardous Decomposition Products: None known (None expected) **Hazardous Polymerization:** Hazardous polymerization will not occur.

Sensitivity to Mechanical Impact: No.

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Serious Eye Damage/Irritation: The eye irritation hazard is based on evaluation of data for product components.

Skin Corrosion/Irritation: The skin irritation hazard is based on evaluation of data for product components.

Skin Sensitization: The skin sensitization hazard is based on evaluation of data for product components.

Acute Dermal Toxicity: The acute dermal toxicity hazard is based on evaluation of data for product components.

Acute Oral Toxicity: The acute oral toxicity hazard is based on evaluation of data for product components.

Acute Inhalation Toxicity: The acute inhalation toxicity hazard is based on evaluation of data for product components. For additional information on the acute toxicity of the components, call the technical information conterns.

Acute Toxicity Estimate: Not Determined

Germ Cell Mutagenicity: The hazard evaluation is based on data for components or a similar material.

Revision Number: 2
Revision Date: October 25, 2019

4 of 7

Delo Syn-Trans XV SAE 75W-80
SDS: 35727

Carcinogenicity: The hazard evaluation is based on data for components or a similar material.

Reproductive Toxicity: The hazard evaluation is based on data for components or a similar material.

Specific Target Organ Toxicity - Single Exposure: The hazard evaluation is based on data for components or a similar material.

Specific Target Organ Toxicity - Repeated Exposure: The hazard evaluation is based on data for components or a similar material.

ADDITIONAL TOXICOLOGY INFORMATION:

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B).

These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY

This material is expected to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

The product has not been tested. The statement has been derived from the properties of the individual components.

MOBILITY

No data available.

PERSISTENCE AND DEGRADABILITY

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Octanol/Water Partition Coefficient: No data available

SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods. (See B.C. Reg. GY/92 Waste Management Act; R.R.O. 1990, Reg. 347 General-Waste Management; C.C.SM.c. W40 The Waste Reduction and Prevention Act; N.S. Reg. 51/95 and N.S. Reg. 179/96 for examples of Provincial legislation.)

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods

 Revision Number:
 2
 Delo Syn-Trans XV SAE 75W-80

 Revision Date:
 October 25, 2019
 Of
 7

Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

TC Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER TRANSPORT CANADA

IMO/IMDG Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE

ICAO/IATA Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO

DOT Shipping Description: NOT REGULATED AS HAZARDOUS MATERIAL UNDER 49 CFR

SECTION 15 REGULATORY INFORMATION

REGULATORY LISTS SEARCHED:

01-1=IARC Group 1 01-2A=IARC Group 2A 01-2B=IARC Group 2B

No components of this material were found on the regulatory lists above.

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), ENCS (Japan), IECSC (China), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (United States).

SECTION 16 OTHER INFORMATION

REVISION STATEMENT: SECTION 01 - Health Emergency information was modified.

SECTION 02 - Environmental Classification information was modified.

SECTION 03 - Composition information was added.

SECTION 03 - Composition information was deleted.

 $SECTION\ 04-Delayed\ Health\ Effects-Reproductive\ Toxicity\ information\ was\ modified.$

SECTION 05 - Fire Fighters Protection Measures information was modified.

SECTION 05 - Special hazards arising from the substance or mixture information was added.

SECTION 08 - Occupational Exposure Limit Table information was modified.

SECTION 08 - Personal Protective Equipment List information was added.

SECTION 09 - Physical/Chemical Properties information was modified.

SECTION 14 - TC Classification information was modified.

SECTION 15 - Chemical Inventories information was modified.

Revision Date: October 25, 2019

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA -	Time Weighted Average				
STEL - Short-term Exposure Limit	PEL -	Permissible Exposure Limit				
GHS - Globally Harmonized System	CAS -	Chemical Abstract Service Number				
ACGIH - American Conference of Governmental	IMO/IMDG	- International Maritime Dangerous				
Industrial Hygienists	Goods Code					
API - American Petroleum Institute	SDS -	Safety Data Sheet				
WHMIS - Workplace Hazardous Materials	NFPA -	National Fire Protection Association (USA)				
Information System						
DOT - Department of Transportation (USA)	NTP -	National Toxicology Program (USA)				

 Revision Number:
 2

 Revision Date:
 October 25, 2019

 6
 of 7

 SDS:
 35727

IARC	-	International Agency for Research on	OSHA	1	-	Occupational	Safety	and	Health
Cancer			Administration						
NCEL	-	New Chemical Exposure Limit	EPA	-	Environmental I	Protection Agency	7		
SCBA	-	Self-Contained Breathing Apparatus							

Prepared according to the WHMIS 2015 by Chevron Energy Technology Company, 6001 Bollinger Canyon Road, San Ramon, CA 94583.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

Revision Number: 2 Delo Syn-Trans XV SAE 75W-80 **7** of 7 Revision Date: October 25, 2019